

1-877-462-7486

VX 680 BRILLIANT PAYMENTS **ANYWHERE**

Go places with Verifone's VX 680. Specifically tailored to the needs of merchants on the move, this full-function, portable payment device is power packed with performance. Businesses from delivery services and stadium vendors to restaurants will benefit from wireless connection options, lightningfast processing speeds and the reliability and security of the proven VX platform.

SMALL DESIGN, BIG PERFORMANCE

- · Delivers wireless connection through GPRS or Wi-Fi/Bluetooth combo or 3G to meet any environment requirement
- Empowers mobile payments with Verifone's NFC software technology
- · Supports loyalty-building, profit-producing and value-added applications
- · Offers maximum security and compliance with end-to-end encryption
- PCI PED 2.0 and PCI PTS 3.0 approved

SPECIFICATIONS

Features

Weight

Security

Dual SIM

GPS

Terminal connectivity

Base connectivity (charging base or

full-feature base with/without battery)

Processor	400 MHz ARM11 32-bit RISC processor
Memory	192MB (128MB Flash, 64MB SDRAM)
Display	3.5" color QVGA resistive touch screen
Printer	18 lps 38mm paper roll
Card Readers	Triple track MSR landed smart card
Contactless	ISO14443 A&B MiFare ISO18092 capable EMVCo L1 certification supports major NFC/contactless schemes
Peripheral Ports	Single multi-port connector supports RS-232, USB Host, USB slave and integrated charging
Other Standard Features	3 SAM slots audio/video player
Power	Battery: Li-Ion 7.2V/1800mAH
Environmental	0° to 50° C (32° to 122° F) operating temperature $~ ~$ -20° to 60° C (-4° to 140° F) storing temperature $~ ~$ 5% to 90% relative humidity, non-condensing
Physical	172mm L x 82mm W x 62mm H

VX 680 GPRS

850/900/1800/1900 MHz

Ethernet Dial modem

UART (via USB dongle)

Terminal: 479g, Full shipping: 1,169g PCI PED 2.0, PCI PTS 3.0

GSM/GPRS

Yes

Yes

eeds of vice is power nd stadium ions, lightning- ven VX platform. oth combo chnology pplications cryption	Image: Select Payment Type Im
o L1 certification USB slave and o 60° C (-4° to 140° F) ondensing	Multiple Connectivity Options Image: Connectivity Image: Con
USB slave and 0 60° C (-4° to 140° F)	Connectivity Options
USB slave and 0 60° C (-4° to 140° F)	Connectivity Options
USB slave and o 60° C (-4° to 140° F) ondensing	Connectivity Options
USB slave and o 60° C (-4° to 140° F) ondensing VX 680 WF/BT Wi-Fi 802.11b/g/n;	Connectivity Options Image: Connectivity Connectivity Maximum Security Image: Connectivity VX 680 3G CSM/GPRS/EDGE: 850/900/1800/1900 MHz
USB slave and o 60° C (-4° to 140° F) ondensing VX 680 WF/BT Wi-Fi 802.11b/g/n; Bluetooth local area	Connectivity Options Image: Connectivity Options Maximum Security Image: Connectivity VX 680 3G Image: Connectivity VX 680 3G SSM/GPRS/EDGE: 850/900/1800/1900 MHz UMTS/HSPA+: 800/850/900/1900/2100 MHz Ethernet, Dial modem, UART (via USB dongle) Image: Connectivity

PORTABLE HARDWARE VERIFONE VX 680

_

© 2015 Verifone, Inc. All rights reserved. Verifone, the Verifone logo and VX are either trademarks or registered trademarks of Verifone in the United States and /or other countries. All other trademarks or brand names are the properties of their respective holders. All features and specifications are subject to change without notice. Product display image for representation purposes only. Actual product display may vary. Reproduction or posting of this document without prior Verifone approval is prohibited. 1/15 1010D_LTR FS

